



## EVO2000 Hyper Series

Twin Modules


700W~1200W

Support 180-518V AC

Up to 170 lm/w

Smart control available

### Specification

Model	EVO2700PLX	EVO2800PLX	EVO2900PLX	EVO21K0PLX	EVO21K1PLX	EVO21K2PLX
System Watts	700W±5%	800W±5%	900W±5%	1000W±5%	1100W±5%	1200W±5%
LED Chips						
CRI	≥70 (Cool White), ≥80 (Natural & Warm White), ≥90 (optional)					
LED nos.	460pcs					
Total Luminous flux (Cool white)	≥119,000 lm ≥170 lm/w	≥134,400 lm ≥168 lm/w	≥144,000 lm ≥160 lm/w	≥160,000 lm ≥160 lm/w	≥173,000 lm ≥158 lm/w	≥186,000 lm ≥155 lm/w
Driver	MeanWell XLG-200, 100~305V AC, 0-10V Dimmable x4		MeanWell XLG-240 100~305V AC, 0-10V Dimmable x4		MeanWell XLG-320 100~305V AC, 0-10V Dimmable x4	
Optional Driver	MeanWell HVG-350H, 180-518V AC, 1-10V x2	MeanWell HVG-240H, 180-518V AC, 1-10V x4			MeanWell HVG-320H, 180-518V AC, 1-10V x4	
Dimming	0-10V (XLG), 1-10V (HLG/HVG)					
Operation Temp.	-40°C~55°C, indoors and outdoors					
IP rating	IP66					
Beam Angle	15°/30°/45°/60°/90°, PC AIO Lens Tear-Drop Technology					
Color Temp.	5000K(CW)/4000K(NW)/ 2700K(WW)					
Dimensions	663x545x146mm (include Straight bracket) 663x545x294mm (include Tilt bracket)					
Weight	29.5 Kg	30.5 Kg			32 Kg	
Material	Die-cast Aluminum Heat-Sink, White/Black painting PC Lens Cover/ UV Cut Stainless 304 Bracket Straight and 30° Tilt bracket (Optional)					
Industrial Certificate	1000hrs Salty-Spray (ASTM B117) testing passed >=62m/sec wind pressure testing passed 3G Vibration /IEC 62471 Photo-biological Safety passed					
Smart Controlling	Neutroni ECO-Link: Zigbee/DALI Neutroni PowerLink: LoRa/NBIOT/LTE/PLC (Power Line Communication)					
Warranty	5 Years, Life Span ≥50,000 hrs					
COO	Made in Taiwan					
Certification	CE/CNS/ROHS					

