




## EVO2000 Hyper Series

Triple Modules  
1350W/1500W/1650W/1800W  
Support 180-518V AC  
Up to 160 lm/w  
Smart control available

Specification				
Model	EVO21K3PLX	EVO21K5PLX	EVO21K6PLX	EVO21K8PLX
System Watts	1350W±5%	1500W±5%	1650W±5%	1800W±5%
LED Chips				
CRI	≥70 (Cool White), >=80 (Natural & Warm White), >=90 (optional)			
LED nos.	690pcs			
Total Luminous flux (Cool white)	≥119,000 lm ≥ 160 lm/w	≥134,400 lm ≥ 160 lm/w	≥144,000 lm ≥ 158 lm/w	≥160,000 lm ≥ 155 lm/w
Driver	MeanWell XLG-240, 100~305V AC, 0-10V Dimmable x6		MeanWell XLG-320 100~305V AC,0-10V Dimmable x6	
Optional Driver	MeanWell HVG-240H, 180-518V AC, 1-10V Dimmable x6		MeanWell HVG-320H, 180-518V AC, 1-10V Dimmablex6	
Dimming	0-10V (XLG), 1-10V (HLG/HVG)			
Operation Temp.	-40°C~55°C, indoors and outdoors			
IP rating	IP66			
Beam Angle	15°/30°/45°/60°/90°, PC AIO Lens Tear-Drop Technology			
Color Temp.	5000K(CW)/4000K(NW)/ 2700K(WW)			
Dimensions	633x832x441mm (include Tilt bracket)			
Weight	42 Kg		46 Kg	
Material	Die-cast Aluminum Heat-Sink, White/Black painting PC Lens Cover/ UV Cut Stainless 304 Bracket Straight and 30° Tilt bracket (Optional)			
Industrial Certificate	1000hrs Salty-Spray (ASTM B117) testing passed >=62m/sec wind pressure testing passed 3G Vibration /IEC 62471 Photo-biological Safety passed			
Smart Controlling	Neutroni ECO-Link: Zigbee/DALI Neutroni PowerLink: LoRa/NBIOT/LTE/PLC (Power Line Communication)			
Warranty	5 Years, Life Span>=50,000 hrs			
COO	Made in Taiwan			
Certification	CE/CNS/ROHS			

